

IN THE CLAIMS

Please amend the claims as follows:

1. (original) A method for operating a speech recognition system (1), in which method a speech signal ( $S_I$ ) of a user is detected and analyzed so as to recognize speech information contained in the speech signal ( $S_I$ ), characterized in that there is determined a reception quality value ( $S_Q$ ) or a noise value which represents a current reception quality, and in that the speech recognition system (1) switches over to a mode of operation which is less sensitive to noise and/or outputs an alert signal ( $S_W$ ) to the user when the reception quality value ( $S_Q$ ) drops below a given reception quality threshold or when the noise value exceeds a noise threshold.

2. (original) A method as claimed in claim 1, characterized in that the speech recognition system is automatically reset to the previous mode of operation when the reception quality value ( $S_Q$ ) exceeds the reception quality threshold again or when the noise value drops below the noise threshold again.

3. (currently amended) A method as claimed in claim 1 ~~or 2~~, characterized in that when the reception quality value drops below

the reception quality threshold or the noise value exceeds the noise threshold, a barge-in mode of operation of the speech recognition system (1) is deactivated.

4. (currently amended) A method as claimed in ~~one of the claims 1 to 3~~claim 1, characterized in that the reception quality value ( $S_Q$ ) or the noise value is determined by means of a voice activity detector (5).

5. (currently amended) A method as claimed in ~~one of the claims 1 to 4~~claim 1, characterized in that the reception quality value ( $S_Q$ ) or the noise value is determined on the basis of a background signal which is received prior to the beginning of the utterance and/or in a speech pause of the user.

6. (currently amended) A method as claimed in claim 4 ~~or 5~~, characterized in that the voice activity detector (5) applies the reception quality value ( $S_Q$ ) or the noise value itself and/or, when the reception quality value drops below the reception quality threshold or when the noise value exceeds the noise threshold, a reception corruption indication signal ( $S_{EB}$ ) to a dialog control device (10).

7. (currently amended) A method as claimed in ~~one of the claims 1 to 6~~claim 1, characterized in that when the reception corruption indication signal ( $S_{EB}$ ) is received and/or when the received reception quality value ( $S_Q$ ) drops below the reception quality threshold or the noise value exceeds the noise threshold, the dialog control device (10) initiates the output of a prompt ( $S_W$ ) to the user who is thus given the information that the reception conditions are poor.

8. (currently amended) A method as claimed in ~~one of the claims 1 to 7~~claim 1, characterized in that an incoming signal is analyzed as regards the type of disturbance causing the reception quality value ( $S_Q$ ) to be below the reception quality threshold or the noise value to be above the noise threshold, and that a prompt ( $S_W$ ) which contains this information is output to the user.

9. (original) A speech recognition system (1) which comprises means (5) for the detection of a speech signal ( $S_I$ ) of a user and a speech recognition device (7) for analyzing the detected speech signal ( $S_I$ ) so as to recognize speech information contained in the speech signal, characterized in that it comprises a quality control device (6) for determining a reception quality value ( $S_Q$ ) or a noise value, representing a current reception quality,

a comparator for comparing the reception quality value ( $S_Q$ ) with a predetermined reception quality threshold or for comparing the noise value with a given noise threshold,

and control means (9, 10) which are constructed in such a manner that the speech recognition system (1) is switched over to a mode of operation which is less sensitive to noise and/or an alert signal ( $S_W$ ) is output to the user when the reception quality value drops below the reception quality threshold or when the noise value exceeds the noise threshold.

10. (currently amended) A computer program which comprises program code means for carrying out all steps of a method as claimed in ~~one of the claims 1 to 8~~claim 1 when the program is run on a computer.